

Old Wood, LLC 425 Bibb Industrial Dr. Las Vegas, New Mexico 87701 (888) 545-9663 Tel: e-mail: Info@OldWood.us www.oldwood.us www.douglasfirfloors.com www.woodblockfloors.com

Fire-Reclaimed & Sourced from:

Native American Tribal Land

Ponderosa Pine Flooring Tongue & Groove Planks



Federal Lands - New Mexico & Colorado			
Other NEPA-Certified Sources			
Product Characteristics	Details		
Description	Solid Wood Flooring with Tongue & Groove available unfinished or pre-finished. All attributes of fire reclaimed wood are present including but not limited to: bug holes (treated), cracks (sound), color variations from board to board, lot to lot and		
Thickness	3/4" (19 mm)		
Length	Random board lengths ranging from 18" long up to 6ft, 8ft, or 10-11 ft. long		
Width	3 1/4" 5 1/4"	7 1/4"	8 1/2"
Grade	Only #1 best grade is used, with "Character" grain & knot pattern		
Finish / Texture Available	Mountain High G		Wire Brushed
Color Choice	- Water & Oil-Based Stains - UV-Cured Oil Top Coat		
Installation	Nailed down or glued to subflooring (wood or concrete slab)		
Provenance	Made in Las Vegas, New Mexico USA		
Use	Residential or Light Commercial		
Warranty	Refer to our website - www.OldWood.us for Warranty details		
Packaging	3 1/4": 27 sq. ft./bundle (54 lbs.) / 900 sq. ft. pallet - 42" x 132" x up to 36" high 5 1/4": 22 sq. ft./bundle (44 lbs.) / 900 sq. ft. pallet - 42" x 132" x up to 36" high 7 1/4": 30 sq. ft./bundle (60 lbs.) / 900 sq. ft. pallet - 42" x 132" x up to 36" high 8 1/2": 32 sq. ft./bundle (64 lbs.) / 900 sq. ft. pallet - 42" x 132" x up to 36" high		
Applicable Standards	R-Value: R-0.7 Formaldehyde Emission (ASTM-E-1333-02): Less than 0.01 ppm Surface Burning (ASTM-E-84): Flame Spread Index of 100-150 Total VOC (ASTM-D-6670-01): 0.003 ppm		
NWFA Janka Test	460 pounds-force (2.0 kilonewtons)		