

Old Wood, LLC
425 Bibb Industrial Drive
Las Vegas, New Mexico 87701
Tel: (888) 545-9663
e-mail: Info@OldWood.us
www.oldwood.us
www.douglasfirfloors.com
www.woodblockfloors.com

## **Product Name: Douglas Fir**

## Sourced from:

Native American Tribal Land Federal Lands - New Mexico & Colorado Other NEPA-Certified Sources

## Douglas Fir Flooring Tongue & Groove Planks



<b>Product Characteristics</b>	Details					
Description	Solid Wood Flooring with Tongue & Groove					
_	Fire-Reclaimed and Available Unfinished or Pre-Finished					
Thickness	3/4" (19 mm)					
Length	Random board lengths ranging from 18" long up to 11 ft. long (longer on req.)					
Width	3 1/4"	5 1/4"	7 1/4"	8 1/2"		
Grade	#1 Character Grade, incl. Flat Sawn & Vertical Grain with all Knots solid & true					
Finish / Texture Available	- Mountain High Grade			- Hand-Scraped		
	- Wire-Brushed			- Circle Sawn		
	- Skip-Planed			- Summit County		
	- Hand-Planed		* 50			
Color Choice	For Pre-Finished boards refer to color charts					
	- Water-Based Stains (16 colors)					
	- UV-Cured Natural Oil Top-Coat					
Installation	Nailed down or glued to subflooring (wood or concrete slab)					
Provenance	Made in Las Vegas, New Mexico USA					
Use	Residential or Light Commercial					
Warranty	Refer to our website - www.OldWood.us for Warranty details					
Packaging	3 1/4": 27 sq ft/bundle (54 lbs.) / 900 sq ft pallet - 42" x 132" x up to 36" high					
	5 1/4": 22 sq ft/bundle (44 lbs.) / 900 sq ft pallet - 42" x 132" x up to 36" high					
	7 1/4": 30 sq ft/bundle (60 lbs.) / 900 sq ft pallet - 42" x 132" x up to 36" high					
	8 1/2": 32 sq ft/bundle (64 lbs.) / 900 sq ft pallet - 42" x 132" x up to 36" high					
Applicable Standards	R-Value: R-0.7					
	Formaldehyde Emission (ASTM-E-1333-02): Less than 0.01 ppm					
	Surface Burning (ASTM-E-84): Flame Spread Index of 100-150					
	Total VOC (ASTM-D-6670-01): 0.003 ppm					